

# PowerBalance 3.0 Designation

RC600B LED40S 840 PSD (ACW) W60L60 GM/CAU

1

2

3

4

5

6

## 1 Lumen package

LED30S – 3100lm

LED40S – 4000lm

## 2 CCT

840 – 4000K

865 – 6500K

## 3 Driver

PSU – Fixed output

PSD - DALI dimming

## 4 Controls

– regular fixed output / DALI

ACW - Actilume wireless 4.1

## 5 Dimension

W60L60 – 597 X 597mm

W30L120 - 297 X 1197mm

W59L59 – 594 X594mm




## 6 GM regular & CAU

GM - regular GM type

CAU – AU/NZ type w. Flex & plug



# Technical Specifications

Type	RC600B LED30S PSU/PSD	RC600B LED30S PSD ACW	RC600B LED40S PSU/PSD/PSD ACW
Picture			
System output	3100lm	3100lm	4000lm
Wattage	24W	25W	32W
System efficacy	130lm/W	124lm/W	125lm/W
UGR	15	15	16
CCT	NW(4000K), CW(6500K)		
CRI	> =80		
SDCM	<= 4		
Operating temp	25°C		
Driver	Fixed output / DALI	DALI (w. Actilume wireless)	Fixed output / DALI / DALI (w.ACW)
IP rating	IP20		
Dimension (mm)	597x597 / 297x1197	597x597 / 297x1197	597x597 / 297x1197
Installation	Recessed (Surface mounted & Suspended as ETO options)		
Lifetime	50,000 hrs @L70 B50		
Approbation	CB / EMC / CE	CB / EMC / CE / ASNZ	CB / EMC / CE / ASNZ